

# SAFETY DATA SHEET

Category 3

# 1. Identification

#### Material name: TREMPRIME WB 1 GL Material: 022053 801

# Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated 3735 Green Road BEACHWOOD OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

# Hazard Classification

# Health Hazards

Skin sensitizer	Category 1
Carcinogenicity	Category 1A

#### **Unknown toxicity - Health**

Acute toxicity, oral	73.66 %
Acute toxicity, dermal	73.38 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	99.81 %

#### **Environmental Hazards**

Acute hazards to the aquatic environment

# Unknown toxicity - Environment

Acute hazards to the aquatic environment	99.6 %
Chronic hazards to the aquatic environment	100 %

#### Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause an allergic skin reaction. May cause cancer. Harmful to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	15 - 40%
Cellulose	9004-34-6	0.5 - 1.5%
Barium boron oxide	13701-59-2	0.1 - 1%
Wood rosin	8050-09-7	0.1 - 1%
Heavy paraffinic distillate	64741-88-4	0.1 - 1%
Clay	1332-58-7	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures



Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air.
Skin Contact:	Get medical attention if symptoms occur. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.
Most important symptoms/effect	s, acute and delayed
Symptoms:	May cause skin and eye irritation.
Indication of immediate medical a	ttention and special treatment needed
Treatment:	Symptoms may be delayed.
5. Fire-fighting measures	
General Fire Hazards:	No unusual fire or explosion hazards noted.
Suitable (and unsuitable) extingu	lishing media
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	
Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.



Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.
7. Handling and storage	
Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities:	Store locked up.

# 8. Exposure controls/personal protection

# **Control Parameters**

#### **Occupational Exposure Limits**

	_		
Chemical Identity	Туре	Exposure Limit Values	Source
Asphalt - Inhalable fraction as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Cellulose	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Cellulose - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Barium boron oxide - as Ba	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Heavy paraffinic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate -	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
Mist.			Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
		particles per	2016)
		cubic foot of	
		air	
Clay - Respirable fraction.	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
		particles per	2016)
		cubic foot of	
		air	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Clay - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03



			2016)
Chemical name	Туре	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Heavy paraffinic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Heavy paraffinic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

0040

## Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.



Hygiene measures:

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

# 9. Physical and chemical properties

Appearance	
Physical state:	liquid
Form:	liquid
Color:	Brown
Odor:	Slight odor
Odor threshold:	No data available.
pH:	9
Melting point/freezing point:	< -0.00 °C < 32 °F
Initial boiling point and boiling range:	> 100 °C > 212 °F
Flash Point:	> 93 °C > 199 °F
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosi	ve limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.022
Solubility(ies)	
Solubility in water:	Dispersible
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

# 10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.



Incompatible Materials:	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

# 11. Toxicological information

Information on likely routes of exposure		
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	May be harmful in contact with skin. May cause an allergic skin reaction.	
Eye contact:	Eye contact is possible and should be avoided.	
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.	

# Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

# Information on toxicological effects

# Acute toxicity (list all possible routes of exposure)

Oral Product:	Not classified for acute toxicity based on available data.
Specified substance(s): Asphalt	LD 50 (Rat): > 5,000 mg/kg
Cellulose	LD 50 (Rat): 5,001 mg/kg
Barium boron oxide	LD 50 (Rat): 850 mg/kg
Wood rosin	LD 50 (Rat): 2,800 mg/kg
Heavy paraffinic distillate	LD 50 (Rat): > 5,000 mg/kg
Clay	LD 50 (Rat): > 5,000 mg/kg

## Dermal



Product:	ATEmix: 2,176.13 mg/kg	
Inhalation Product:	Not classified for acute toxicity based on available data.	
Specified substance(s): Asphalt	LC 50 (Rat): > 94.4 mg/m3	
Cellulose	LC 50 (Rabbit): 20.1 mg/l	
Barium boron oxide	LC 50 (Rat): > 21.7 mg/l	
Heavy paraffinic distillate	LC 50 (Rat): 2.18 mg/l	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
Specified substance(s): Asphalt	in vivo (Rabbit): Not irritant Experimental result, Key study	
Barium boron oxide	in vivo (Rabbit): Not irritant Experimental result, Key study	
Wood rosin	in vivo (Rabbit): Not irritant Experimental result, Key study	
Heavy paraffinic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study	
Serious Eye Damage/Eye Irritati Product: Specified substance(s):	<b>on</b> No data available.	
Asphalt	Rabbit, 24 hrs: Not irritating	
Wood rosin	Rabbit, 24 hrs: Irritating	
Heavy paraffinic distillate	Rabbit, 24 hrs: Not irritating	

# Respiratory or Skin Sensitization Product: No data available.



Carcinogenicity Product:	No data available.	
IARC Monographs on	e Evaluation of Carcinogenic Ris	ks to Humans:
Asphalt	Overall evaluation: Possi	bly carcinogenic to humans.
Heavy par distillate	inic Overall evaluation: Not c evaluation: Carcinogenic	assifiable as to carcinogenicity to humans. Overall to humans.
<b>US. National Toxicolo</b> Heavy distillate	<b>Program (NTP) Report on Carci</b> ı ıraffinic Known To Be Human Ca	
	egulated Substances (29 CFR 19 nponents identified	010.1001-1050):
Germ Cell Mutagenicit		
In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specific Target Organ Product:	<b>oxicity - Single Exposure</b> No data available.	
Specific Target Organ Product:	<b>oxicity - Repeated Exposure</b> No data available.	
Aspiration Hazard Product:	No data available.	
Other effects:	No data available.	



# 12. Ecological information

# **Ecotoxicity:** Acute hazards to the aquatic environment: Fish **Product:** No data available. Specified substance(s): Barium boron oxide LC 50 (Harlequinfish, red rasbora (Rasbora heteromorpha), 96 h): 0.145 mg/I Mortality **Aquatic Invertebrates** Product: No data available. Chronic hazards to the aquatic environment: Fish **Product:** No data available. Specified substance(s): Asphalt NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study **Aquatic Invertebrates** Product: No data available. **Toxicity to Aquatic Plants** Product: No data available. Persistence and Degradability Biodegradation Product: No data available. **BOD/COD** Ratio Product: No data available. **Bioaccumulative potential Bioconcentration Factor (BCF)** Product: No data available. Partition Coefficient n-octanol / water (log Kow) **Product:** No data available.



Mobility in soil:	No data available. Harmful to aquatic organisms.	
Other adverse effects:		
13. Disposal considerations		
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.	
Contaminated Packaging:	No data available.	
14. Transport information		

#### TDG:

Not Regulated

#### CFR / DOT:

Not Regulated

#### IMDG:

Not Regulated

# 15. Regulatory information

# **US Federal Regulations**

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.

# CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Barium boron oxide	1000 lbs.
Sodium hydroxide	1000 lbs.
Hydrogen sulfide	100 lbs.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard



#### SARA 302 Extremely Hazardous Substance

-	<b>Reportable</b>
Chemical Identity	quantity
Hydrogen sulfide	100 lbs.

Threshold Planning Quantity 500 lbs.

# SARA 304 Emergency Release Notification

ortable quantity
bs.
lbs.
lbs.
bs.

# SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Hydrogen sulfide	500lbs
Asphalt	10000 lbs
Cellulose	10000 lbs
Barium boron oxide	10000 lbs
Wood rosin	10000 lbs
Heavy paraffinic distillate	10000 lbs
Clay	10000 lbs

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity	Reportable quantity
Hydrogen sulfide	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) None present or none present in regulated quantities.

## **US State Regulations**

## **US. California Proposition 65**



#### WARNING

Cancer - www.P65Warnings.ca.gov

## US. New Jersey Worker and Community Right-to-Know Act

# Chemical Identity

Asphalt Heavy paraffinic distillate

# US. Massachusetts RTK - Substance List

Chemical Identity Asphalt Hydrogen sulfide



# US. Pennsylvania RTK - Hazardous Substances <u>Chemical Identity</u> Asphalt

# US. Rhode Island RTK Chemical Identity

Asphalt

#### International regulations

# Montreal protocol

Not applicable

#### Stockholm convention

Not applicable

# **Rotterdam convention**

Not applicable

# Kyoto protocol

Not applicable

# VOC:

Regulatory VOC (less water and exempt solvent)	:	2 g/l
VOC Method 310	:	0.09 %



Inventory Status: Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	2.1
Further Information:	No data available.



**Disclaimer:** 

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.