

Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/21/2015

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : ALPHAGUARD BIO BASE COAT PART A 5 GAL

Product code : 351700AT805

COMPANY : Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST Emergency Phone : (216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Gray. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.

Eyes : Direct contact may cause mild irritation.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Low acid filtered neutral oil	8001-79-4	40.0 - 70.0
Talc	14807-96-6	10.0 - 30.0
Fire retardant	NJ TSRN# 51721300-5035P	10.0 - 30.0
Calcium carbonate	471-34-1	7.0 - 13.0
Calcium oxide	1305-78-8	5.0 - 10.0
Fire retardant	NJ TSRN# 51721300-5036P	3.0 - 7.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1.0
Aluminum oxide	1344-28-1	0.1 - 1.0



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/21/2015

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

medical attention.

Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.

Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If

irritation, rash or other disorders develop, get medical attention immediately.

Ingestion : Get medical attention. Do not induce vomiting.

Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not available. Method : Not applicable.

Burning rate : Non-Flammable Liquid

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : This product is not expected to burn under normal conditions of use.

Hazardous combustion

Protective equipment for

products

Carbon monoxide and carbon dioxide can form. Smoke, fumes.

: Use accepted fire fighting techniques. Wear full firefighting protective

firefighters clothing, including self-contained breathing apparatus (SCBA).

Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

An **RPIT** Company 2/7 351700AT805



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/21/2015

Respiratory protection : Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA

approved respirator with combination particulate filter and vapor/gas

removing cartridge when the ventilation is not adequate or if it is necessary to

abrade or grind surfaces coated with this product.

Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to

reduce exposure.

Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face

shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily

available.

Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.

Protective measures : Other equipment not normally required. Use professional judgment in the

selection, care, and use.

Engineering measures : Not required under normal conditions of use. Use local exhaust when the

general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Talc	14807-96-6	ACGIH TWA:	2 mg/m3	Respirable fraction.
		OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
Fire retardant	NJ TSRN# 51721300-5035P	ACGIH TWA:	1 mg/m3	Respirable fraction.
Calcium oxide	1305-78-8	ACGIH TWA:	2 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA:	10 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Hydrotreated heavy naphthenic distillate	64742-52-5	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Aluminum oxide	1344-28-1	ACGIH TWA:	10 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	1 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquid Color : Gray

pH : Not available.

Vapour pressure : Not available.

Vapor density : Heavier than air



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/21/2015

Melting point/range : Not available. Freezing point : Not available. Boiling point/range : Not available.

Water solubility : Soluble Specific Gravity : 1.37 % Volatile Weight : 0%

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids. Strong bases.

Stability : Stable

Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Aluminum hydroxide, CAS-No.: 21645-51-2

Acute oral toxicity (LD-50 oral) 5,000 mg/kg (Rat) > 15,900 mg/kg (Rat) > 2,000 mg/kg (

Rat) > 2,000 mg/kg (Rat) > 10,000 mg/kg (Rat)

0.888 mg/l for 4 h (Rat) 10 mg/m3 for 4 h (Rat) > 2.3 mg/l Acute inhalation toxicity (LC-50)

for 4 h (Rat) 7.6 mg/l for 1 h (Rat) > 0.888 mg/l for 4 h (

Rat)

Calcium carbonate, CAS-No.: 471-34-1

Acute oral toxicity (LD-50 oral) 6,450 mg/kg (Rat) 1,300 mg/kg (Mouse) > 2,000 mg/kg (

Rat) > 2,000 mg/kg (Rat)

Acute inhalation toxicity (LC-50) > 3 mg/l for 4 h (Rat)

Acute dermal toxicity (LD-50 dermal) > 2,000 mg/kg (Rat)

Calcium oxide, CAS-No.: 1305-78-8

790 mg/kg (Rat) 250 mg/kg (Rabbit) 2,045 mg/kg (Acute oral toxicity (LD-50 oral)

Mouse) 500 mg/kg (Rabbit) 180.6 - 361.1 mg/kg (Rabbit) 2,000 mg/kg (Rabbit) 1,000 mg/kg (Rabbit) 4,179 mg/kg (Rat) 500 - 1,000 mg/kg (Rabbit) 1,940 mg/kg (Mouse) 3,798 mg/kg (Rat) >= 7,340 mg/kg (Rat) >= 7,300 mg/kg

(Mouse) > 2,000 mg/kg (Rat)

40 mg/m3 for 4 h (Rat) 1,026 mg/m3 for 1 h (Rat) 160 Acute inhalation toxicity (LC-50)

mg/m3 for 4 h (Rat)

Acute dermal toxicity (LD-50 dermal) > 2,500 mg/kg (Rabbit) > 5,000 mg/kg (Rabbit)

Titanium dioxide, CAS-No.: 13463-67-7

> 25,000 mg/kg (Rat) > 11,000 mg/kg (Rat) > 2,000 mg/kgAcute oral toxicity (LD-50 oral)

(Rat) > 5,000 mg/kg (Rat) > 5,000 mg/kg (Rat)

Acute inhalation toxicity (LC-50) > 3.56 mg/l for 4 h (Rat) > 2.28 mg/l for 4 h (Rat) 3.43 mg/l

for 4 h (Rat) 5.09 mg/l for 4 h (Rat) > 6.82 mg/l for 4 h (

Rat)

Hydrotreated heavy naphthenic distillate, CAS-No.: 64742-52-5

Acute oral toxicity (LD-50 oral) 5,000 mg/kg (Rat) > 2,000 mg/kg (Rat) > 5,000 mg/kg (

Rat) > 5,000 mg/kg (Rat) > 5,000 mg/kg (Rat)



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/21/2015

Acute inhalation toxicity (LC-50) > 3.9 mg/l for 4 h (Rat) > 5.3 mg/l for 4 h (Rat) > 5.2 mg/l

for 4 h $\,$ (Rat) > 5.53 mg/l for 4 h $\,$ (Rat) 2.18 mg/l for 4 h $\,$ (Rat) > 5 mg/l for 4 h $\,$ (Rat) > 5.2 mg/l for 4 h $\,$ (Rat) 10.5 mg/l for 4 h $\,$ (Rat) 10.5 mg/l for 4 h $\,$ (Rat) 5.7 mg/l for 4 h $\,$ (Rat) 5.7 mg/l for 4 h $\,$ (Rat) > 2.4 mg/l for 4 h $\,$ (Rat) 9.6 mg/l for 4 h $\,$ (Rat) > 5.3 mg/l for 4 h $\,$ (Rat) > 6 mg/l for 4 h $\,$ (Rat) > 5 mg/l for 4 h $\,$ (Rat) > 5 mg/l for 4 h $\,$ (Rat) > 4.7 mg/l for 4 h $\,$ (Rat) > 2.5 mg/l for 4 h $\,$ (Rat) > 3.9 mg/l for 4 h $\,$ (Rat)

Acute dermal toxicity (LD-50 dermal) > 2,000 mg/kg (Rabbit) > 5,000 mg/kg (Rabbit) > 5,000

mg/kg (Rabbit) > 2,000 mg/kg (Rabbit) > 3,000 mg/kg (

Rabbit)

Aluminum oxide, CAS-No.: 1344-28-1

Acute oral toxicity (LD-50 oral) > 15,900 mg/kg (Rat) > 10,000 mg/kg (Rat) > 2,000 mg/kg

(Rat) > 2,000 mg/kg (Rat)

Acute inhalation toxicity (LC-50) > 2.3 mg/l for 4 h (Rat) 0.888 mg/l for 4 h (Rat) > 0.888

mg/l for 4 h (Rat) 7.6 mg/l for 1 h (Rat) 10 mg/m3 for 4 h

(Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local

regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

An **RPITI** Company 5/7 351700AT805



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/21/2015

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components None present or none present in regulated quantities.

SARA 311/312 Hazards Acute Health Hazard

Chronic Health Hazard

OSHA Hazardous Components:

Talc 14807-96-6

Fire retardant NJ TSRN# 51721300-5035P

Calcium oxide 1305-78-8 Titanium dioxide 13463-67-7 Hydrotreated heavy naphthenic distillate 64742-52-5 Aluminum oxide 1344-28-1

OSHA Status: Considered hazardous based on the

following criteria:

: Irritant Carcinogen

OSHA Flammability : Not Regulated

Regulatory VOC (less water and

exempt solvent)

: 1 g/l

VOC Method 310 : 0.07 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Hydrotreated heavy naphthenic distillate 64742-52-5

U.S. State Regulations:

MASS RTK Components 14807-96-6 Talc

> Calcium carbonate 471-34-1 Calcium oxide 1305-78-8 Titanium dioxide 13463-67-7

Penn RTK Components Low acid filtered neutral oil 8001-79-4 14807-96-6

Talc

Fire retardant NJ TSRN# 51721300-5035P

Calcium carbonate 471-34-1 Calcium oxide 1305-78-8

NJ TSRN# 51721300-5036P Fire retardant

Titanium dioxide 13463-67-7

NJ RTK Components Low acid filtered neutral oil 8001-79-4

> Talc 14807-96-6

Fire retardant NJ TSRN# 51721300-5035P

Calcium carbonate 471-34-1 Calcium oxide 1305-78-8 Titanium dioxide 13463-67-7 Hydrotreated heavy naphthenic distillate 64742-52-5

Components under California Proposition 65:

RPM Company 6/7 351700AT805



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/21/2015

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum
Flammability	1	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System