

Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/22/2015

## **SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : ALPHAGUARD BIO TOP COAT PART B - 1 GAL

Product code : 351710BT801

COMPANY : Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST Emergency Phone : (216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use : Coating

## **SECTION 2 - HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Clear, light yellow to yellow. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

#### **Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and

throat. May cause moderate irritation to the respiratory system. May cause allergic

respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal

irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

#### **Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

#### **Chronic Health Effects**

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Eye, Lung, Liver, Kidney, Skin, Nerve

## **SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %	
Homopolymer of HDI	28182-81-2	> 60.0	
Hexamethylene diisocyanate (HD	822-06-0	0.1 - 1.0	



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/22/2015

#### SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be

performed by trained personnel.Leave area to breathe fresh air. Avoid further

overexposure. If symptoms persist, get medical attention.

Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical

attention immediately.

Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If

irritation, rash or other disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

## **SECTION 5 - FIRE FIGHTING MEASURES**

Flash point : 174 °C, 345 °F Method : Setaflash Closed Cup

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.

Hazardous combustion : Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Closed

container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition

and flashback.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

## **SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store under dry warehouse conditions away from heat and all ignition sources.





Version 1.0 Print Date 01/22/2015

**REVISION DATE: 01/22/2015** 

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Personal protection equipment**

Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when

airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator

(TC19C or equivalent) for isocyanates.

Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to

reduce exposure.

Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face

shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily

available.

Skin and body protection : Prevent contact with shoes and clothing.

Protective measures : Use professional judgment in the selection, care, and use.

Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed

areas. Use local exhaust when the general ventilation is inadequate.

#### **Exposure Limits**

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Hexamethylene	822-06-0	ACGIH TWA:	0.005 ppm	
diisocyanate (HD				

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquid

Color : Clear, light yellow to yellow

Odor : Solvent

pH : Not available.

Vapour pressure : Not available.

Vapor density : Heavier than air

Melting point/range : Not available.

Freezing point : Not available.

Boiling point/range : Not available.

Water solubility : Negligible

Specific Gravity : 0.95 % Volatile Weight : 0 %

## SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids. Strong bases. Amines. Water or moisture. Alcohols.



Version 1.0 Print Date 01/22/2015

**REVISION DATE: 01/22/2015** 

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur under normal conditions.

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

Hexamethylene diisocyanate (HD, CAS-No.: 822-06-0

Acute oral toxicity (LD-50 oral) 1,980 mg/kg (Mouse) 960 mg/kg (Rat) 1,100 mg/kg (Cat

) 959 mg/kg (Rat) 1,979 mg/kg (Mouse) 350 mg/kg (Mouse) 746 mg/kg (Rat) 710 mg/kg (Rat) 1,050 mg/kg (

Cat ) 940 mg/kg (Rat)

Acute inhalation toxicity (LC-50) 40 mg/l for 1 h ( Rat ) 22 mg/l for 4 h ( Rat ) 0.03 mg/l for 2 h

) 614 mg/m3 for 6 h (Rat) 310 mg/m3 for 4 h (Rat)

Acute dermal toxicity (LD-50 dermal) 593 mg/kg (Rabbit) 570 mg/kg (Rabbit) > 7,000 mg/kg (

Rat ) 599 mg/kg (Rabbit) > 525 mg/kg (Rat)

#### **SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under

RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in

compliance with federal, state and local regulations.

## **SECTION 14 - TRANSPORTATION / SHIPPING DATA**

#### CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated



Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/22/2015

## **SECTION 15 - REGULATORY INFORMATION**

#### **North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:** 

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components:

Hexamethylene diisocyanate (HD 822-06-0

OSHA Status: Considered

hazardous based on the

following criteria:

: Irritant

OSHA Flammability : Not Regulated

Regulatory VOC (less water and

exempt solvent)

: Not available.

VOC Method 310 : Not available.

U.S. State Regulations:

Penn RTK Components : Homopolymer of HDI 28182-81-2

NJ RTK Components : Homopolymer of HDI 28182-81-2

Components under California Proposition 65:

None known.

#### **SECTION 16 - OTHER INFORMATION**

#### **HMIS Rating:**

Health	1	0 = Minimum
Flammability	1	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

#### **Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.





Version 1.0 Print Date 01/22/2015

REVISION DATE: 01/22/2015

Prepared by: Rich Mikol

Lagand

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and

Liability Act

**DOT - Department of Transportation** 

DSL - Domestic Substance List EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System