

SOLARGARD HY-BUILD WHITE 5 GAL PL

Version 6.0
REVISION DATE: 06/16/2014

Print Date 07/23/2014

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : SOLARGARD HY-BUILD WHITE 5 GAL PL

Product code : 1512700005P

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
Emergency Phone : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

White. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
Eyes : Direct contact may cause mild irritation.
Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Overexposure to sublimed zinc oxide may produce symptoms known as "zinc oxide chills" which have no recognized complications. Symptoms usually disappear within 24 hours. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	30.0 - 60.0
Calcium carbonate	471-34-1	15.0 - 40.0
Acrylic polymer(s)	NJ TSRN# 51721300-5434P	15.0 - 40.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Propylene glycol	57-55-6	1.0 - 5.0
Zinc oxide	1314-13-2	1.0 - 5.0



SOLARGARD HY-BUILD WHITE 5 GAL PL

Version 6.0
 REVISION DATE: 06/16/2014

Print Date 07/23/2014

Inert Filler	NJ TSRN# 51721300-5013P	1.0 - 5.0
Aluminum oxide	1344-28-1	0.1 - 1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0
Ammonium hydroxide	1336-21-6	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Get medical attention. Do not induce vomiting.
- Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not applicable.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.



SOLARGARD HY-BUILD WHITE 5 GAL PL

Version 6.0
 REVISION DATE: 06/16/2014

Print Date 07/23/2014

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Zinc oxide	1314-13-2	ACGIH TWA: ACGIH STEL: OSHA PEL: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 10 mg/m3 5 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable fraction. Fume. Respirable fraction. Total dust. Total dust. Respirable fraction.
Inert Filler	NJ TSRN# 51721300-5013P	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction.
Aluminum oxide	1344-28-1	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: ACGIH TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3 1 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction. Respirable fraction.

SOLARGARD HY-BUILD WHITE 5 GAL PL

Version 6.0

Print Date 07/23/2014

REVISION DATE: 06/16/2014

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
Ammonium hydroxide	1336-21-6	ACGIH TWA: ACGIH STEL: OSHA PEL:	25 ppm 35 ppm 35 mg/m3	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: White
Odor	: Mild Ammonia
pH	: 9 - 10
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 212 °F, 100 °C
Water solubility	: Soluble
Specific Gravity	: 1.33
% Volatile Weight	: 34 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Strong acids.Strong bases.
Stability	: Stable
Hazardous polymerization	: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Calcium carbonate, CAS-No.: 471-34-1 Acute oral toxicity (LD-50 oral)	6,450 mg/kg (Rat)
Titanium dioxide, CAS-No.: 13463-67-7 Acute oral toxicity (LD-50 oral)	25,000 mg/kg (Rat) 5,000 mg/kg (Rat) 5,000 mg/kg (Rat) 2,000 mg/kg (Rat) 11,000 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	> 6.82 mg/l for 4 h (Rat) 3.43 mg/l for 4 h (Rat) 5.09 mg/l for 4 h (Rat) > 2.28 mg/l for 4 h (Rat) > 3.56 mg/l for 4 h (Rat)



SOLARGARD HY-BUILD WHITE 5 GAL PL

Version 6.0

Print Date 07/23/2014

REVISION DATE: 06/16/2014

Propylene glycol, CAS-No.: 57-55-6 Acute oral toxicity (LD-50 oral)	30,000 mg/kg (Rat) 18,000 mg/kg (Rabbit) 19,000 mg/kg (Dog) 23,900 - 31,800 mg/kg (Mouse) 18,400 - 196,000 mg/kg (Guinea pig)
Zinc oxide, CAS-No.: 1314-13-2 Acute oral toxicity (LD-50 oral)	7,950 mg/kg (Mouse) 7,950 mg/kg (Mouse)
Ammonium hydroxide, CAS-No.: 1336-21-6 Acute oral toxicity (LD-50 oral)	350 mg/kg (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
One or more components are listed on the NDSL.

U.S. Federal Regulations:

SARA 313 Components	:	Zinc oxide	1314-13-2
SARA 311/312 Hazards	:	Acute Health Hazard Chronic Health Hazard	



SOLARGARD HY-BUILD WHITE 5 GAL PL

Version 6.0
 REVISION DATE: 06/16/2014

Print Date 07/23/2014

OSHA Hazardous Components :

Titanium dioxide	13463-67-7
Zinc oxide	1314-13-2
Inert Filler	NJ TSRN# 51721300-5013P
Aluminum oxide	1344-28-1
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Ammonium hydroxide	1336-21-6

OSHA Status: Considered : Irritant
 hazardous based on the Carcinogen
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 22 g/l
 exempt solvent)

VOC Method 310 : 0.89 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components	:	Calcium carbonate	471-34-1
		Titanium dioxide	13463-67-7
		Zinc oxide	1314-13-2
		Inert Filler	NJ TSRN# 51721300-5013P
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
		Ammonia	7664-41-7
		Acrylamide	79-06-1
		Acrylonitrile	107-13-1
		Acetaldehyde	75-07-0
		p-Dioxane	123-91-1
	Ethylene oxide	75-21-8	

Penn RTK Components	:	Water	7732-18-5
		Calcium carbonate	471-34-1
		Acrylic polymer(s)	NJ TSRN# 51721300-5434P
		Titanium dioxide	13463-67-7
		Propylene glycol	57-55-6
		Zinc oxide	1314-13-2
		Inert Filler	NJ TSRN# 51721300-5013P

NJ RTK Components	:	Water	7732-18-5
		Calcium carbonate	471-34-1
		Acrylic polymer(s)	NJ TSRN# 51721300-5434P
		Titanium dioxide	13463-67-7
		Propylene glycol	57-55-6
		Zinc oxide	1314-13-2
		Inert Filler	NJ TSRN# 51721300-5013P
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm



SOLARGARD HY-BUILD WHITE 5 GAL PL

Version 6.0
 REVISION DATE: 06/16/2014

Print Date 07/23/2014

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 DOT - Department of Transportation
 DSL - Domestic Substance List
 EPA - Environmental Protection Agency
 HMIS - Hazardous Materials Information System
 IARC - International Agency for Research on Cancer
 MSHA - Mine Safety Health Administration
 NDSL - Non-Domestic Substance List
 NIOSH - National Institute for Occupational Safety and Health
 NTP - National Toxicology Program
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act
 RTK - Right To Know
 SARA - Superfund Amendments and Reauthorization Act
 STEL - Short Term Exposure Limit
 TLV - Threshold Limit Value
 TSCA - Toxic Substances Control Act
 TWA - Time Weighted Average
 V - Volume
 VOC - Volatile Organic Compound
 WHMIS - Workplace Hazardous Materials Information System