

Pebble Tread Walkpad

Solid rubber, non-skid protective pad for light foot traffic



FEATURES

- Non-Slip surface
- Thick, solid rubber
- High Quality material

BENEFITS

- Safer traffic across roof areas
- Protects roof membrane from damage
- Long lasting Protection

DESCRIPTION

Pebble Tread Walkpads are a solid rubber protective pad with a non-skid diamond textured surface.

BASIC USES

Recommended for use on Built-up, MB, and single ply roof systems for light foot traffic. Suitable for use as a roof top service pathway, around roof top equipment, and under light equipment supports.

DIMENSIONS

3' x 4' x 3/4" (914mm x 1219mm x 19mm) Nominal. (Actual 35.75" +/- 0.5" x 47.5" +/- 0.5" x 0.70" +/- 0.05" (908 +/- 13mm x 1206 +/- 13 mm x 18 +/- 1mm)).

PACKAGING

50 pads per pallet

COLOR

Black

WEIGHT

Approximately 49 lbs (22.2 kg) each

APPLICATION

Prior to installation, turn over and lay out each Pebble Tread Walkpad for approximately 30 minutes to allow for moisture to dissipate from the surface. Use a circular saw to cut to desired size.

Adhere Pebble Tread Walkpads to a flat surface in ribbons or spot applications of the following adhesives:

- Polyroof SF
- Reglet Joint Sealant
- Sheeting Bond, Black
- Solargard Seam Sealer

Apply positive pressure during installation to assure positive contact. Space pads 1" to 3" (25-75mm) or in a stepping stone pattern to permit water flow across the roof surface.

LIMITATIONS

Not intended to be surfaced with reflective roof coatings.

Not intended for application over aggregate roof surfaces.

Not intended for exposure to oil, gasoline, or mineral spirits bases solvents. Rubber compound may swell and permanently deform.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE	TEST METHOD
Ultimate Elongation	80%	ASTM D412
Tensile Strength	600 psi	ASTM D412
Shore A Hardness	64	ASTM D2240
Specific Gravity	1.06-1.15	ASTM D297
Tear Resistance	117 lbs/in	ASTM D624

Pebble Tread Walkpad

MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



Roofing & Building Maintenance

www.tremcoroofing.com

3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

220 Wicksteed Avenue
Toronto, Ontario M3H 1G7
1.800.668.9879

Tremco Roofing and Building
Maintenance is part of Tremco
Construction Products Group

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.