

Tremco AVC Membrane Primers

Quick Drying Primers for Use with Tremco AVC Membranes

DESCRIPTION

Tremco AVC Membrane Primer is an SIS rapid-curing adhesive primer formulated to prepare and promote adhesion to sound, clean and dry structural decks and subdecks of concrete, metal, wood and exterior grade sheathing panels. Tremco AVC Primer should be applied with a roller or brush prior to application of Tremco AVC Membrane. Apply Tremco AVC Membrane after Tremco AVC Primer dries to a non-transferable tacky film. (approximately 15 minutes at 23°C at 50% relative humidity)

Tremco AVC Membrane Primer (WB) is a water-based (WB), quick drying modified bitumen primer to be applied prior to the application of Tremco AVC Membrane. WB promotes adhesion to sound, clean and dry structural decks and subdecks of concrete, metal, wood and exterior grade sheathing panels. Apply Tremco AVC Membrane Primer (WB) with a brush or roller. Tremco AVC Membrane should not be applied to Tremco AVC Membrane Primer (WB) until it is completely dry (approximately 45 minutes at 23°C at 50% relative humidity). Stir primer before use. Do not apply Tremco AVC Membrane Primer (WB) below 7°C. (45°F).

PACKAGING

18.9L (5 gal) pails

COVERAGE RATES

Approximately 6m²/Lm (250 ft²/gal) depending on porosity and texture of surface.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE	TEST METHOD
Tremco AVC Membrane Primer		
% Total solids	44.5-46.5	
Viscosity	500-750 cps	
Specific gravity	0.89-0.91	
Appearance	Dark green, light syrupy liquid	
Tremco AVC Membrane Primer (WB)		
% Total solids	53.3 (4 lb.)	
Viscosity	2-3600 cps	
Specific gravity	0.89-0.91	
Appearance		

Tremco AVC Membrane Primers

MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



www.tremcoroofing.com
3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

50 Beth Nealson Drive
Toronto, Ontario M4H 1M6
1.800.668.9879

Tremco Roofing & Building
Maintenance is a part of the Tremco
Construction Products Group

Tremco is a US Registered trademark of Tremco Incorporated.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.