

Roofing and Building Maintenance

PRODUCT SPECIFICATION DATA SHEET

VR HydroPaver

PRECAST PAVERS FOR USE ON PATIOS AND WALKWAYS

PRODUCT DESCRIPTION

Description Pavers with water retention and

drainage characteristics for patios

and walkways. Best used in

conjunction with VR PaverPedestals.

Options Available in different colors.



PRODUCT PROPERTIES

Materials Ceramics

Dimensions

Width x Length 11.81 in x 23.62 in (30cm x 60cm)

Thickness 2.17 in (55 mm)

Weight 41.8 lb (19 kg)

Water Retention 0.15 Gal/ft² (6 L/m²)

Will absorb a 1/4 in rain event.

Compressive STR 66.8 MPa (9,690 psi)

Complies with CSA A231.2-14 and ASTM C936

Freeze-Thaw Durability

49 Cycles Negligible

Infiltration Rate Ave. 88.2 in/hr (2,240 mm/hr)

In accordance to ASTM C1781

SSD Density 127 lb/ft³ (2,034 kg/m³)

In accordance to CSA A23.2-11C

Absorption 6.9%

In accordance to CSA A23.2-11C



PRODUCT SPECIFICATION DATA SHEET

VR HydroPaver

PRECAST PAVERS FOR USE ON PATIOS AND WALKWAYS

GUARANTEE / WARRANTY

Tremco Incorporated warrants VR HydroPaver to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any VR HydroPaver product that is proved to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge.

THIS IS BUYER'S SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



Tremco Incorporated www.tremcoinc.com

UNITED STATES 3735 Green Road Beachwood, OH 44122 1.800.562.2728 CANADA 50 Beth Nealson Drive Toronto, ON M4H 1M6 T: 1.800.668.9879