

**PRODUCT DESCRIPTION**

**Description** Pavers for patios and walkways. Best used in conjunction with VR PaverPedestals.

**Options** Available in different colors & textures.


**PRODUCT PROPERTIES**

**Materials** Concrete

**Dimensions**

**Width x Length** 24 in x 24in (60.9cm x 60.9cm)

**Thickness** 1.75 in (44.5 mm)  
2 in (50.8 mm)  
2.25 in (57.1 mm)  
2.5 in (63.5 mm)

**Weight**

137 lb/ft<sup>3</sup> (2,194.5 kg/m<sup>3</sup>)

**Compression Strength**

Min 8,000 psi (55MPa)

**Compressive STR**

Min 725 psi (5MPa)

**Freeze-Thaw Durability**

Less than 1% loss after 40 cycles.

**Absorption**

Less than 5%.

# PRODUCT SPECIFICATION DATA SHEET

## VR Paver

PRECAST PAVERS FOR  
USE ON ROOFTOPS

### GUARANTEE / WARRANTY

Tremco Incorporated warrants VR Paver to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any VR Paver product that is proved to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge.

THIS IS BUYER'S SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**Tremco Incorporated**  
www.tremcoinc.com

UNITED STATES  
3735 Green Road  
Beachwood, OH 44122  
1.800.562.2728

CANADA  
50 Beth Neilson Drive  
Toronto, ON M4H 1M6  
T: 1.800.668.9879