

TremLock® Invisa-Lap Panel

Exposed fastener wall and roof panel



FEATURES

- Nearly invisible lap
- Patent and Copyright Protected

BENEFITS

- Aesthetically pleasing
- Great selling point

DESCRIPTION

The TremLock Invisa-Lap panel is a patented and copyright protected panel that can't be copied and features a nearly invisible lap offering a distinctive look.

BASIC USES

TremLock Invisa-Lap Panel is an exposed fastener wall panel used on slopes down to 3:12. Tape sealant is required on seam (side laps.)

DETAILS

Standard panel lengths up to 40'. Please inquire for longer lengths.

SYSTEM DESIGN

TremLock Invisa-Lap panels are designed 36" wide coverage in length with multiple corrugations; 3/4" high, 9" on center with minor corrugations between each major corrugation the entire length of the panel.


FINISH/COLOR

- Acrylic coated Galvalume®
- Fluoropolymer (Kynar 500® PVDF resin-based)
- Siliconized Polyester and Polyester
- Oil canning is inherent in all metal panels and is not cause for panel rejection

APPLICATION

TremLock Invisa-Lap panels are installed over plywood or purlins. All exposed fasteners shall be pre-painted to match roof or wall panel colors.

SECTION PROPERTIES & PROFILES



Fastener Pattern (@ Eaves, Ridges & Endlaps):



(@ Intermediate Purlins):



Foam Inside Closure:



Foam Outside Closure:



TESTING

TITLE OF TEST	TEST METHOD
Uplift Testing	UL 580 Class 90
Impact Resistance	UL 2218 Class 4

TremLock® Invisa-Lap Panel

MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



Roofing & Building Maintenance

www.tremcoroofing.com

3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

50 Beth Neelson Drive
Toronto, Ontario M4H 1M6
1.800.668.9879

Tremco is a US Registered trademark of Tremco Incorporated.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.

TremLock® is a U.S. registered trademark of Tremco Incorporated.

Kynar 500® is a U.S. registered trademark of Arkema Inc.

Hylar 5000® is a U.S. registered trademark of Solvay Solexis, Inc.

Galvalume® is a U.S. registered trademark of BIEC International Inc.

Fluoropon® is a U.S. registered trademark of SWIMC LLC.