

# TremLock® Mini-Rib Panel

## Exposed fastener wall panel

### FEATURES

Architectural

### BENEFITS

- Modern design



## DESCRIPTION

TremLock Mini-Rib wall panels are factory roll formed 24 or 26 gauge Galvalume® steel, zinc coated by hot-dip process per ASTM A792/A792M. The Galvalume panel is coated with Kynar 500® / Hylar 5000®. Refer to color chart for available colors.

## BASIC USES

TremLock Mini-Rib wall panel is an exposed fastener wall panel that can be used as an exterior wall cover and is excellent for use with parapet wall applications. A variety of fastener options are available to meet the needs of appearance and different substrate attachment. Appealing profile for wall, soffit, liner and fascia applications.

## DETAILS

Standard panel lengths up to 40'. Please inquire for longer lengths. TremLock Mini-Rib is not applicable for exterior roof panels.

## SYSTEM DESIGN

TremLock Mini-Rib panels are designed 36" wide coverage up to 40' in length with multiple corrugations; 3/8" high 3" on center with minor corrugations between each of the major corrugations the entire length of panel.

## FINISH/COLOR


TremLock Mini-Rib roof & wall panels with factory applied finish.  
Kynar 500 (PVDF).  
Silicone Modified Polyester (SMP).

Oil canning is inherent in all metal panels and is not cause for panel rejection.

## APPLICATION

TremLock Mini-Rib panels are installed over solid substrate or spanning members (hat channels). All exposed fasteners shall be prepainted to match panel colors. All side laps shall be at least one full corrugation. Panels are sealed at the base of wall with metal closures.

## PANEL OPTIONS



## MAINTENANCE

Your local Tremco Roofing Sales Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

## PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

## TECHNICAL SUPPORT



Roofing & Building Maintenance

[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013

50 Beth Nealson Drive  
Toronto, Ontario M4H 1M6  
1.800.668.9879

Tremco is a US Registered trademark of Tremco Incorporated.

The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.

TremLock® is a U.S. registered trademark of Tremco Incorporated.  
Kynar 500® is a U.S. registered trademark of Arkema Inc.  
Hylar 5000® is a U.S. registered trademark of Solvay Solexis, Inc.  
Galvalume® is a U.S. registered trademark of BIEC International Inc.  
Fluoropon® is a U.S. registered trademark of SWIMC LLC.