

TremLock® CP Panel

Concealed fastener canopy panel

FEATURES

- Strength
- Hidden Fasteners

BENEFITS

- Limited framing needed
- Flush/flat panel



DESCRIPTION

TremLock CP Panels are concealed fastener canopy panels that are factory roll formed.
Standard: 24 GA. ASTM A792 (50 ksi steel) AZ55 - Bare, AZ50 - Painted.

BASIC USES

TremLock CP Panels are designed to be used as concealed fastener canopy panels, over plywood, hat section, mac-girts, or open framing.

SYSTEM DESIGN

Continuous lengths up to 40'. Please inquire for longer lengths. 12" or 16" Flat Pan.




FINISH/COLOR

TremLock CP Panels are available in acrylic-coated Galvalume® and fluoropolymer (Kynar 500® PVDF resin-based). Oil canning is inherent in all metal panels and is not cause for panel rejection.

APPLICATION

TremLock CP Panels are designed to meet the demands of canopy installations such as banks, drive-throughs or any building type that requires an attractive and functional canopy system.

SECTION PROPERTIES & PROFILES



MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



www.tremcoroofing.com
 3735 Green Road
 Beachwood, Ohio 44122
 1.800.852.6013
 50 Beth Nealson Drive
 Toronto, Ontario M4H 1M6
 1.800.668.9879

Tremco is a US Registered trademark of Tremco Incorporated.
 The information provided on this data page supersedes all previous data concerning this product and its application.
 The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.
 TremLock® is a U.S. registered trademark of Tremco Incorporated.
 Kynar 500® is a U.S. registered trademark of Arkema Inc.
 Hylar 5000® is a U.S. registered trademark of Solvay Solexis, Inc.
 Galvalume® is a U.S. registered trademark of BIEC International Inc.
 Fluoropon® is a U.S. registered trademark of SWIMC LLC.