

# TremLock® IL Panel

## Standing Seam Metal Roof System

### FEATURES

Snap seam

### BENEFITS

- Does not need to be seamed



### DESCRIPTION

TremLock IL Panel is a factory roll formed metal roof system that is manufactured from standard - 24 GA. ASTM A792 (50 ksi) or optional - 22 GA. ASTM A792 (50 ksi).

### BASIC USES

The TremLock IL Panel is a roof panel used in light construction applications.

### SYSTEM DESIGN

TremLock IL Panel may be applied over a substrate of plywood or metal deck.

### FINISH/COLOR


Acrylic Coated Galvalume®  
 Fluoropolymer (Kynar 500® PVDF resin-based)  
 Oil canning is inherent in all metal panels and is not cause for panel rejection.

### APPLICATION


Non-structural panel used on roof slopes of 3:12 or greater. Continuous lengths up to 80ft. Plank, striated, and minor ribs.

### SECTION PROPERTIES & PROFILES


#### Plank:




#### Striations Profile:



#### Minor Rib Profile:




#### Seam Engagement:




#### Clip:


24 GA. -  
 ASTM A792 (50 ksi)



#### Stackable Leveling Shim:



#### Bearing Plate:



### PHYSICAL PROPERTIES

#### TITLE OF TEST

#### TEST METHOD

Uplift

UL 580 Class 90, UL 1897

Impact Resistance

UL Class 4, UL 2218

Fire Rating

UL Class A

Texas Windstorm

RC-86

# TremLock® IL Panel

## MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

## PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

## TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013

50 Beth Neelson Drive  
Toronto, Ontario M4H 1M6  
1.800.668.9879

Tremco is a US Registered trademark of Tremco Incorporated.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.

TremLock® is a U.S. registered trademark of Tremco Incorporated.

Kynar 500® is a U.S. registered trademark of Arkema Inc.

Hylar 5000® is a U.S. registered trademark of Solvay Solexis, Inc.

Galvalume® is a U.S. registered trademark of BIEC International Inc.

Fluoropon® is a U.S. registered trademark of SWIMC LLC.