

DynaRound Hatch Guard

AVAILABLE THROUGH
TREMCO
 Roofing & Building Maintenance



Self-closing gate prevents accidental entry.



Width adjustable to allow for hatch size variations.



Unique compression fit design. No drilling!



Rugged hinges allow gate tension adjustment.

All Rooftop entry/exit points must be protected. The DynaRound Hatch Guard provides a non-penetrating, affordable solution. With easy setup, our hatch protection system can be used for both temporary and permanent solutions. The adjustable, self-closing gate prevents accidental entrance.

The DynaRound Hatch Guard is designed to install quickly. The unique snap in place rails allow typical installation in less than 60 minutes with 2 people.

The DynaRound Hatch Guard mounts directly to the roof hatch with a compression fit design. No drilling necessary means rooftop water integrity is not compromised. Multiple sizes are available to fit almost any hatch. Yellow or gray FRP posts and guardrails with galvanized fittings and self closing gate ensure a long service life.

SPECIFICATIONS

Safety Ratings

OSHA Requirements:

- 1926.501(b)(4)
- 1910.28(b)
- 1926.502(b)
- 1910.29(b)

CAL/OSHA Requirements:

- 3209
- 3212

IBC 2015 Requirements:

- 1015.3
- 1015.7
- 1607.8.1.1
- 1015.4.4
- 1607.8.1
- 1607.8.1.2

National Building Code of Canada 2015

- 4.1.5.14
- 9.8.8.2

Benefits

- Fast Installation
- Rugged Design
- Compression Fit
- No Cutting or Drilling
- Self-Closing Gate
- FRP Posts and Rails
- No Roof Penetration
- Adjustable - Fits Nearly Any Roof Hatch
- Custom Configurations Available

Measurements

- Rail Heights
 - Top Rail Height: 42"
 - Mid Rail Height: 20"
- Multiple Sizes Available
 - 30-36" x 30-54"
 - 42-48" x 42-60"
 - 30-36" x 96-114"
- Custom Sizes Available

