

DynaRound Slimline Warning Lines

HEAVY-DUTY (HD) WARNING LINES



This permanent warning system includes heavy-duty base plates, plastic coated cable and rigid, plastic pennants. The heavy-duty stanchions and bases are designed to withstand years of use. The standard system includes three stanchions, three bases, and 100 feet of cable with plastic flags.

SPECIFICATIONS

Safety Ratings

OSHA Requirements:

- 1926.501(b)(10)
- 1910.28(b)(8)(ii)
- 1926.502(f)
- 1910.29(d)

OH&S:

- R.R.O. 1990, Reg. 851, s. 85 (b)(i)

Alberta OSHA 2009:

- Section 161

Features and Benefits

- Permanent warning line system used for visual warning of at-risk areas
- Uses heavy-duty, galvanized, weighted bases; steel cable; and rigid, plastic pennants
- Stanchions and bases can be purchased individually for non-linear installations requiring multiple turns.

Components

Set up with a Base Plate Every 25' with Pennants

Standard Kit includes:

- 3 - 42" Stanchions
- 3 - Base Plates
- 100' of Plastic Coated Cable

LIGHT-DUTY (LD) WARNING LINES



Create a safe-zone using the LD Warning Line System. Generally used for temporary warning line applications, our LD system features folding stanchions with a nylon line and vinyl flags that can be set up quickly. The lightweight folding stanchions and flagged nylon cord can be installed easily. Typical installation for warning lines requires lines be placed a minimum of six feet from hazard for construction applications. (See your individual state OSHA regulations for compliance.)

SPECIFICATIONS

Safety Ratings

OSHA Requirements:

- 1926.501(b)(10)
- 1910.28(b)(8)(ii)
- 1926.502(f)
- 1910.29(d)

OH&S:

- R.R.O. 1990, Reg. 851, s. 85 (b)(i)

Alberta OSHA 2009:

- Section 161

Features and Benefits

- Foldable warning line system used for visual warning of at risk areas
- Standard system includes 3 folding bases and 100 feet of flags
- Optional transporter holds up to 9 folding warning line systems
- Optional rubber feet attachments

Components

Standard Kit Includes:

- 3 - 39.5" Stanchions, 48" x 45" Footprint, 36 lbs.
- 100 Feet of Nylon Flagged Line with Flags Every 5' Nylon Cord Rated at 657 lbs. Tensile Strength