

Tremco TPA Single Ply Roofing Systems Unreinforced Flashing Membrane

DESCRIPTION

TPA unreinforced membrane - 55 mils thick

BASIC USES

The unreinforced, monolithic TPA Flashing Membrane is designed for use to tie in the roof drain to the Reinforced TPA field membrane. TPA Flashing Membrane can also be used to secure seams, penetrations, and TPA metal overlaps which require an additional placement of TPA membrane over the top to enhance watertightness of the TPA roof system.

SIZE

Roll dimension of 24" x 30'

PACKAGING

Available in rolls.

APPLICATION

Installation Procedures:

1. Install TPA Field membrane over drain.
2. Cut a target ply of TPA Flashing Membrane to center over the drain.
3. Insert the target ply of TPA Flashing Membrane under the TPA Field Membrane and smooth sheet to minimize wrinkles.
4. Heat weld target ply of TPA Flashing Membrane to TPA Field Membrane.
5. Cut out center of TPA Flashing Membrane target ply to expose drain.
6. Apply urethane sealant on top of metal drain bowl lip edge.
7. Install Drain clamping ring over TPA Flashing Membrane target and secure.

MAINTENANCE

Your local Tremco Roofing Sales Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Roofing Sales Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



www.tremcoroofing.com

3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

50 Beth Nealson Drive
Toronto, Ontario M4H 1M6
1.800.668.9879

Tremco Roofing & Building
Maintenance is a part of the Tremco
Construction Products Group

Tremco is a US Registered trademark of Tremco Incorporated.

The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.