

TremPly® TPO Vent Boot

A Molded Accessory Designed for TremPly TPO Single Ply Roof Systems



FEATURES

Cost effective

Factory-built accessories

Uniform look

Same high-heat properties as our TremPly TPO membranes

BENEFITS

- Reduces installed costs by up to 25% compared to field fabrication
- Improved reliability, reduces risk of leaks and callbacks
- Improved aesthetics
- Proven performance

DESCRIPTION

TremPly® TPO Vent Boots provide roofing contractors with an easy-to-install factory-built detail. TremPly TPO Vent Boots are manufactured using a proprietary formulation that is designed for use with Tremco's high-performance TremPly TPO single-ply membranes.

BASIC USES

TremPly TPO Vent Boots eliminate the need for contractors to fabricate boots in the field. They are molded from a proprietary TPO formulation engineered to work with TremPly TPO single-ply membranes. TremPly TPO Vent Boots come in one standard size and accommodate most common pipes and conduits; They are supplied with stainless steel clamping rings.

COLORS

White, gray and tan

SIZE

Membrane thickness 0.065" (1.65 mm). For pipes 1" - 6" (25.4 - 152 mm) dia.

PACKAGING

6 Vent boots per carton.; Weight 9 lbs (4.1 kg) per carton; TremPy Max TPO Vent Boot, 48 Cases per pallet. TremPly TPO Vent Boot, 54 cases per pallet.

APPLICATION

TremPly TPO Vent Boots are designed for use with TremPly Max TPO, and TremPly TPO. They may be installed on TremPly TPO 45, 60, and 80 mil mechanically attached or fully adhered roofing systems and TremPly Max TPO 50, 60, 70, and 80 mil mechanically attached or fully adhered roofing systems. See published application and specification manual for detailed information.

MAINTENANCE

PRECAUTIONS

TECHNICAL SUPPORT

TremPly® TPO Vent Boot

Your local Tremco Roofing Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.



Roofing & Building Maintenance

www.tremcoroofing.com

3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

50 Beth Nealson Drive
Toronto, Ontario M4H 1M6
1.800.668.9879

Tremco Roofing & Building
Maintenance is a part of the Tremco
Construction Products Group

Tremco is a US Registered trademark of Tremco Incorporated.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.