



## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Product Identification

**Product ID:** SPA0375X  
Product Name: MATTE BLACK WEATHERX  
Product Use: Paint product.  
Print date: 01/Feb/2010  
Revision Date: 01/Feb/2010

#### Company Identification

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

**Manufacturer's Phone:** 1-612-332-7371

**24-Hour Medical Emergency Phone:** 1-888-345-5732

### 2. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Eye Contact:

- Severe eye irritation
- Risk of serious damage to eyes.

#### Skin Contact:

- May cause defatting of the skin.
- Dermatitis
- Causes skin irritation.
- Harmful if absorbed through skin.
- Can be absorbed through skin.
- May cause sensitization by skin contact.

#### Ingestion:

- Irritation of the mouth, throat, and stomach.
- Harmful if swallowed.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

#### Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.

- May cause damage to nasal and respiratory passages.
- May cause chemical pneumonia.
- May cause sensitization by inhalation.
- May cause pulmonary edema.
- May cause bronchopneumonia or bronchitis.
- Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

**Target Organ and Other Health Effects:**

- Kidney injury may occur.
- Causes headache, drowsiness or other effects to the central nervous system.
- Liver injury may occur.
- Blood disorders
- Risk of serious damage to the lungs (by inhalation).
- Unconsciousness
- Spleen damage may occur.
- Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Possible sensitization.
- Contains formaldehyde which is considered a potential carcinogen by the Occupational Health and Safety Administration.

**Teratogens:**

- May cause birth defects.
- Contains material that may cause adverse reproductive effects.

**Carcinogens:**

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>Chemical Name</b>
C.I. PIGMENT BLACK 26 68186-94-7	10 - 15	C.I. Pigment Black 26
AROMATIC NAPHTHA, HEAVY 64742-94-5	5 - 10	Solvent naphtha, petroleum, heavy arom.
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	5 - 10	2-Butoxyethanol
AROMATIC NAPHTHA, LIGHT 64742-95-6	5 - 10	Petroleum naphtha, light aromatic
1,2,4-TRIMETHYLBENZENE 95-63-6	1 - 5	1,2,4-Trimethylbenzene
TITANIUM DIOXIDE 13463-67-7	1 - 5	Titanium dioxide
PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE 108-65-6	1 - 5	2-methoxy-1-methylethyl acetate

### 3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

DIETHYLENE GLYCOL BUTYL ETHER 112-34-5	1 - 5	Diethylene glycol monobutyl ether
C.I. PIGMENT BLACK 7 1333-86-4	1 - 5	Carbon black
DIACETONE ALCOHOL 123-42-2	1 - 5	Diacetone alcohol
NAPHTHALENE 91-20-3	1 - 5	Naphthalene
FORMALDEHYDE 50-00-0	0 - .099	Formaldehyde

If this section is blank there are no hazardous components per OSHA guidelines.

### 4. FIRST AID MEASURES

#### Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

#### Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

#### Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

#### Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Place unconscious person on the side in the recovery position and ensure breathing.

#### Medical conditions aggravated by exposure:

Any respiratory or skin condition.

### 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	120
Flash point (Celsius):	49
Lower explosive limit (%):	1
Upper explosive limit (%):	16
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

#### Unusual fire and explosion hazards:

None known.

#### Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

#### Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

### Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

## 7. HANDLING AND STORAGE

### Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### Personal Protective Equipment

#### Eye and face protection:

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

#### Skin protection:

Appropriate chemical resistant gloves should be worn.

#### Other Personal Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

#### Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

### Exposure Guidelines

#### OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
C.I. PIGMENT BLACK 26 68186-94-7	10 - 15		= 5 mg/m <sup>3</sup> Ceiling Mn	
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	5 - 10	240 mg/m <sup>3</sup> TWA 50 ppm TWA		prevent or reduce skin absorption

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
TITANIUM DIOXIDE 13463-67-7	1 - 5	15 mg/m <sup>3</sup> TWA dust total		
C.I. PIGMENT BLACK 7 1333-86-4	1 - 5	3.5 mg/m <sup>3</sup> TWA		
DIACETONE ALCOHOL 123-42-2	1 - 5	240 mg/m <sup>3</sup> TWA 50 ppm TWA		
NAPHTHALENE 91-20-3	1 - 5	10 ppm TWA 50 mg/m <sup>3</sup> TWA		
FORMALDEHYDE 50-00-0	0 - .099	0.75 ppm TWA		

#### ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
C.I. PIGMENT BLACK 26 68186-94-7	10 - 15	0.2 mg/m <sup>3</sup> TWA Mn			
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	5 - 10	20 ppm TWA			
1,2,4-TRIMETHYLBENZENE 95-63-6	1 - 5	25 PPM			
TITANIUM DIOXIDE 13463-67-7	1 - 5	10 mg/m <sup>3</sup> TWA			
C.I. PIGMENT BLACK 7 1333-86-4	1 - 5	3.5 mg/m <sup>3</sup> TWA			
DIACETONE ALCOHOL 123-42-2	1 - 5	50 ppm TWA			
NAPHTHALENE 91-20-3	1 - 5	10 ppm TWA	15 ppm STEL		CAN BE ABSORBED THROUGH THE SKIN
FORMALDEHYDE 50-00-0	0 - .099			0.3 ppm Ceiling	

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	3.6842105 mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	5.6
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	10.19
Specific Gravity:	1.22
Evaporation rate (butyl acetate = 1.0):	0.34
Flash point (Fahrenheit):	120
Flash point (Celsius):	49
Lower explosive limit (%):	1
Upper explosive limit (%):	16
Autoignition temperature:	not determined

## 10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Conditions to Avoid:

Heat.

Incompatibility:

Strong oxidizing agents

Hazardous Polymerization:

None anticipated.

Hazardous Decomposition Products:

Carbon monoxide and carbon dioxide. Metal oxide fumes.  
Nitrogen compounds. formaldehyde

**Sensitivity to static discharge:**

Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
AROMATIC NAPHTHA, HEAVY 64742-94-5	5 - 10	> 2000 mg/kg Dermal LD50 Rabbit > 5000 mg/kg Oral LD50 Rat > 590 mg/m <sup>3</sup> Inhalation LC50 Rat 4 h
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	5 - 10	= 2.21 mg/L Inhalation LC50 Rat 4 h = 220 mg/kg Dermal LD50 Rabbit = 2270 mg/kg Dermal LD50 Rat = 450 ppm Inhalation LC50 Rat 4 h = 470 mg/kg Oral LD50 Rat
AROMATIC NAPHTHA, LIGHT 64742-95-6	5 - 10	= 3400 ppm Inhalation LC50 Rat 4 h = 8400 mg/kg Oral LD50 Rat > 2000 mg/kg Dermal LD50 Rabbit > 5.2 mg/L Inhalation LC50 Rat 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	1 - 5	= 18 g/m <sup>3</sup> Inhalation LC50 Rat 4 h = 3400 mg/kg Oral LD50 Rat > 3160 mg/kg Dermal LD50 Rabbit
TITANIUM DIOXIDE 13463-67-7	1 - 5	> 10000 mg/kg Oral LD50 Rat
PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE 108-65-6	1 - 5	= 8532 mg/kg Oral LD50 Rat > 5000 mg/kg Dermal LD50 Rabbit
DIETHYLENE GLYCOL BUTYL ETHER 112-34-5	1 - 5	= 2700 mg/kg Dermal LD50 Rabbit = 3384 mg/kg Oral LD50 Rat
C.I. PIGMENT BLACK 7 1333-86-4	1 - 5	> 15400 mg/kg Oral LD50 Rat > 3 g/kg Dermal LD50 Rabbit
DIACETONE ALCOHOL 123-42-2	1 - 5	= 13500 mg/kg Dermal LD50 Rabbit = 4 g/kg Oral LD50 Rat
NAPHTHALENE 91-20-3	1 - 5	= 490 mg/kg Oral LD50 Rat > 20 g/kg Dermal LD50 Rabbit > 2500 mg/kg Dermal LD50 Rat > 340 mg/m <sup>3</sup> Inhalation LC50 Rat 1 h
FORMALDEHYDE 50-00-0	0 - .099	= 0.578 mg/L Inhalation LC50 Rat 4 h = 500 mg/kg Oral LD50 Rat

### Mutagens/Teratogens/Carcinogens:

Possible mutagen

May cause birth defects. Contains material that may cause adverse reproductive effects.

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

IARC has classified carbon black as possibly carcinogenic to humans (Group 2B). Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
NAPHTHALENE 91-20-3	1 - 5		Listed. initial date 4/19/02 - carcinogen
FORMALDEHYDE 50-00-0	0 - .099		Listed. initial date 1/1/88 - carcinogen

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
TITANIUM DIOXIDE 13463-67-7	1 - 5			Monograph 47 [1989]
C.I. PIGMENT BLACK 7 1333-86-4	1 - 5			Monograph 65 [1996]
NAPHTHALENE 91-20-3	1 - 5			Monograph 82 [2002]
FORMALDEHYDE 50-00-0	0 - .099	Supplement 7 [1987] Monograph 62 [1995] Supplement 7 [1987]		

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	5 - 10			male rat-no evidence; female rat-equivocal evidence; male mice- some evidence; female mice-some evidence
TITANIUM DIOXIDE 13463-67-7	1 - 5			male rat-negative; female rat-negative; male mice-negative; female mice-negative
NAPHTHALENE 91-20-3	1 - 5		Reasonably Anticipated To Be A Human Carcinogen	male rat-clear evidence; female rat-clear evidence; male mice-no evidence; female mice- some evidence
FORMALDEHYDE 50-00-0	0 - .099		Reasonably Anticipated To Be A Human Carcinogen	

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	5 - 10			A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans
TITANIUM DIOXIDE 13463-67-7	1 - 5	Present		
C.I. PIGMENT BLACK 7 1333-86-4	1 - 5	Present		

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
NAPHTHALENE 91-20-3	1 - 5	Present		
FORMALDEHYDE 50-00-0	0 - .099	Present	Irritant and potential cancer hazard - see 29 CFR 1910.1048	A2 Suspected Human Carcinogen

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

UN ID Number (msds): UN1263  
 Proper Shipping Name: PAINT  
 Hazard Class: COMBUSTIBLE LIQUID  
 Packing Group: III

### U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### Reportable Quantity Description:

### International Air Transport Association (IATA):

UN ID Number (msds): UN1263  
 Proper Shipping Name: Paint  
 Hazard Class: 3  
 Packing Group: III

### International Maritime Organization (IMO):

IMO UN/ID Number (msds): UN1263  
 Proper Shipping Name: PAINT  
 Hazard Class: 3  
 Packing Group: III

## 15. REGULATORY INFORMATION

### U.S. FEDERAL REGULATIONS:

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
C.I. PIGMENT BLACK 26 68186-94-7	10 - 15		YES	
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	5 - 10		YES	
1,2,4-TRIMETHYLBENZENE 95-63-6	1 - 5		Listed.	



## 15. REGULATORY INFORMATION

DIETHYLENE GLYCOL BUTYL ETHER 112-34-5	1 - 5		YES	
NAPHTHALENE 91-20-3	1 - 5		form R reporting required for 1.0% de minimis concentration	100
FORMALDEHYDE 50-00-0	0 - .099	EPCRA RQ = 100 lb	form R reporting required for 0.1% de minimis concentration	100

### SARA 311/312 Hazard Class:

Acute: yes  
Chronic: yes  
Flammability: yes  
Reactivity: no  
Sudden Pressure: no

### U.S. STATE REGULATIONS:

#### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

#### California Proposition 65:

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### Rule 66 status of product

Not photochemically reactive.

### INTERNATIONAL REGULATIONS - Chemical Inventories

#### US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

#### Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

## 16. OTHER INFORMATION

### HMIS Codes

**Health:** 2\*  
**Flammability:** 2  
**Reactivity:** 1  
**PPE:** X - See Section 8 for Personal Protective Equipment (PPE).

### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

Prepared By:	Regulatory Affairs Department
Print date:	01/Feb/2010
Revision Date:	01/Feb/2010