



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: 436B194
Product Name: FLPN REGAL BLUE
Product Use: Paint product.
Print date: 04/Feb/2010
Revision Date: 04/Feb/2010

Company Identification

The Valspar Corporation
PO Box 1461
Minneapolis, MN 55440

Manufacturer's Phone: 1-612-332-7371

24-Hour Medical Emergency Phone: 1-888-345-5732

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Eye Contact:

- Severe eye irritation

Skin Contact:

- May cause defatting of the skin.
- Causes skin irritation.
- Harmful if absorbed through skin.
- Can be absorbed through skin.
- May cause sensitization by skin contact.

Ingestion:

- Irritation of the mouth, throat, and stomach.
- Harmful if swallowed.

Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- May cause damage to nasal and respiratory passages.
- May cause sensitization by inhalation.
- May cause pulmonary edema.
- May cause chemical pneumonia.

Target Organ and Other Health Effects:

- Kidney injury may occur.
- Causes headache, drowsiness or other effects to the central nervous system.
- Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.
- Liver injury may occur.
- Risk of serious damage to the lungs (by inhalation).
- Unconsciousness

This product contains ingredients that may contribute to the following potential chronic health effects:

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Possible sensitization.
- Contains formaldehyde which is considered a potential carcinogen by the Occupational Health and Safety Administration.

Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE 108-65-6	15 - 20	2-methoxy-1-methylethyl acetate
ISOPHORONE 78-59-1	15 - 20	Isophorone
C.I. PIGMENT BLUE 28 1345-16-0	10 - 15	C.I. Pigment Blue 28
DIMETHYL PHTHALATE 131-11-3	1 - 5	Dimethyl phthalate
ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2	1 - 5	Ethylene glycol, monobutyl ether acetate
DIETHYLENE GLYCOL BUTYL ETHER 112-34-5	1 - 5	Diethylene glycol monobutyl ether
C.I. PIGMENT BLACK 28 68186-91-4	1 - 5	C.I. Pigment Black 28
TITANIUM DIOXIDE 13463-67-7	1 - 5	Titanium dioxide
C.I. PIGMENT GREEN 50 68186-85-6	.1 - 1	COBALT TITANATE GREEN SPINEL
FORMALDEHYDE 50-00-0	0 - .099	Formaldehyde

If this section is blank there are no hazardous components per OSHA guidelines.

4. FIRST AID MEASURES

4. FIRST AID MEASURES

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention immediately.

Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Place unconscious person on the side in the recovery position and ensure breathing.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	83
Flash point (Celsius):	28
Lower explosive limit (%):	1
Upper explosive limit (%):	13
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid all personal contact.

7. HANDLING AND STORAGE

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Chemical goggles, also wear a face shield if splashing hazard exists.

Skin protection:

Gloves: Neoprene or other nonporous.

Other Personal Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas. Chemical resistant apron

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
ISOPHORONE 78-59-1	15 - 20	140 mg/m ³ TWA 25 ppm TWA		
C.I. PIGMENT BLUE 28 1345-16-0	10 - 15	0.1 MG/m ³		
DIMETHYL PHTHALATE 131-11-3	1 - 5	5 mg/m ³ TWA		
C.I. PIGMENT BLACK 28 68186-91-4	1 - 5	0.5 mg/m ³ TWA Cr		
TITANIUM DIOXIDE 13463-67-7	1 - 5	15 mg/m ³ TWA dust total		
FORMALDEHYDE 50-00-0	0 - .099	0.75 ppm TWA		

ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
ISOPHORONE 78-59-1	15 - 20			5 ppm Ceiling	

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
C.I. PIGMENT BLUE 28 1345-16-0	10 - 15	0.02 mg/m ³ Co			
DIMETHYL PHTHALATE 131-11-3	1 - 5	5 mg/m ³ TWA			
ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2	1 - 5	20 ppm TWA			
C.I. PIGMENT BLACK 28 68186-91-4	1 - 5	0.5 mg/m ³ TWA Cr			
TITANIUM DIOXIDE 13463-67-7	1 - 5	10 mg/m ³ TWA			
C.I. PIGMENT GREEN 50 68186-85-6	.1 - 1	0.02 mg/m ³ Co			
FORMALDEHYDE 50-00-0	0 - .099			0.3 ppm Ceiling	

9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	3.6842105 mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	6.69
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	10.92
Specific Gravity:	1.31
Evaporation rate (butyl acetate = 1.0):	0.34
Flash point (Fahrenheit):	83
Flash point (Celsius):	28
Lower explosive limit (%):	1
Upper explosive limit (%):	13
Autoignition temperature:	not determined

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Heat.
Incompatibility:	Strong oxidizing agents
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Metal oxide fumes. Ammonia compounds. Nitrogen compounds.

Sensitivity to static discharge: Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s

11. TOXICOLOGICAL INFORMATION

PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE 108-65-6	15 - 20	= 8532 mg/kg Oral LD50 Rat > 5000 mg/kg Dermal LD50 Rabbit
ISOPHORONE 78-59-1	15 - 20	= 1390 mg/kg Dermal LD50 Rat = 1870 mg/kg Oral LD50 Rat = 7 mg/L Inhalation LC50 Rat 4 h
DIMETHYL PHTHALATE 131-11-3	1 - 5	= 6800 mg/kg Oral LD50 Rat > 20 mL/kg Dermal LD50 Rabbit > 4800 mg/kg Dermal LD50 Rat
ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2	1 - 5	= 1480 mg/kg Dermal LD50 Rabbit = 1600 mg/kg Oral LD50 Rat
DIETHYLENE GLYCOL BUTYL ETHER 112-34-5	1 - 5	= 2700 mg/kg Dermal LD50 Rabbit = 3384 mg/kg Oral LD50 Rat
TITANIUM DIOXIDE 13463-67-7	1 - 5	> 10000 mg/kg Oral LD50 Rat
FORMALDEHYDE 50-00-0	0 - .099	= 0.578 mg/L Inhalation LC50 Rat 4 h = 500 mg/kg Oral LD50 Rat

Mutagens/Teratogens/Carcinogens:

Possible mutagen

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

The International Agency For Research On Cancer (IARC) has determined that Cobalt and Cobalt Compounds are substances that are possibly carcinogenic to humans (IARC group 2B). Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA. Nickel and certain nickel compounds: There is sufficient evidence of the carcinogenicity of nickel and nickel compounds (NTP-1985) also, (IARC 1976, vol. 11) states there is sufficient evidence for the carcinogenicity of certain nickel compounds. Nickel subsulfide is carcinogenic in rats by inhalation, producing lung cancer. Nickel compounds (nickel powder, subsulfide, oxide, carbonate, and nickelocene) produced local sarcomas in mice, rats and hamsters when given intramuscularly. Inhalation of nickel carbonyl produced a low incidence of lung tumors in rats. Contains chromates which may cause cancer.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
FORMALDEHYDE 50-00-0	0 - .099		Listed. initial date 1/1/88 - carcinogen

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
C.I. PIGMENT BLUE 28 1345-16-0	10 - 15			Monograph 52 [1991]
TITANIUM DIOXIDE 13463-67-7	1 - 5			Monograph 47 [1989]
C.I. PIGMENT GREEN 50 68186-85-6	.1 - 1			Monograph 52 [1991]
FORMALDEHYDE 50-00-0	0 - .099	Supplement 7 [1987] Monograph 62 [1995] Supplement 7 [1987]		

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
ISOPHORONE 78-59-1	15 - 20			male rat-some evidence; female rat-no evidence; male mice-equivocal evidence; female mice- no evidence
TITANIUM DIOXIDE 13463-67-7	1 - 5			male rat-negative; female rat-negative; male mice-negative; female mice-negative
FORMALDEHYDE 50-00-0	0 - .099		Reasonably Anticipated To Be A Human Carcinogen	

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
ISOPHORONE 78-59-1	15 - 20			A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans
C.I. PIGMENT BLUE 28 1345-16-0	10 - 15	Present		Group A3 Confirmed animal carcinogen with unknown relevance to humans.
ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2	1 - 5			A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans
TITANIUM DIOXIDE 13463-67-7	1 - 5	Present		
C.I. PIGMENT GREEN 50 68186-85-6	.1 - 1	Present		
FORMALDEHYDE 50-00-0	0 - .099	Present	Irritant and potential cancer hazard - see 29 CFR 1910.1048	A2 Suspected Human Carcinogen

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

UN ID Number (msds): UN1263
 Proper Shipping Name: PAINT
 Hazard Class: 3
 Packing Group: III
 Hazardous Ingredient (Land) 1 PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE

14. TRANSPORTATION INFORMATION

U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Reportable Quantity Description:

International Air Transport Association (IATA):

UN ID Number (msds): UN1263
Proper Shipping Name: Paint
Hazard Class: 3
Packing Group: III
IATA N.O.S. Technical Name 1 PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE

International Maritime Organization (IMO):

IMO UN/ID Number (msds): UN1263
Proper Shipping Name: PAINT
Hazard Class: 3
Packing Group: III
IMDG N.O.S. Technical Name 1 PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
ISOPHORONE 78-59-1	15 - 20			5000
C.I. PIGMENT BLUE 28 1345-16-0	10 - 15		YES	
DIMETHYL PHTHALATE 131-11-3	1 - 5		form R reporting required for 1.0% de minimis concentration	5000
ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 112-07-2	1 - 5		YES	
DIETHYLENE GLYCOL BUTYL ETHER 112-34-5	1 - 5		YES	
C.I. PIGMENT BLACK 28 68186-91-4	1 - 5		YES	
C.I. PIGMENT GREEN 50 68186-85-6	.1 - 1		YES	
FORMALDEHYDE 50-00-0	0 - .099	EPCRA RQ = 100 lb	form R reporting required for 0.1% de minimis concentration	100

SARA 311/312 Hazard Class:

Acute: yes
Chronic: yes
Flammability: yes
Reactivity: no
Sudden Pressure: no

U.S. STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

California Proposition 65:

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of product

Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories**US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

16. OTHER INFORMATION**HMIS Codes**

Health:	2*
Flammability:	3
Reactivity:	1
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

Prepared By:	Regulatory Affairs Department
Print date:	04/Feb/2010
Revision Date:	04/Feb/2010